# Bev E<sup>x</sup>PRESS<sup>™</sup>

# MULTI-PLATE SHEET FILTER

ErtelAlsop's externally ported filters are designed for small to middle sized wineries, breweries, distillers, and the food and beverage market in general.

ErtelAlsop's BW and ME Filters are superior quality, low cost, multiplate sheet filters consists of a 304 stainless steel frames mounted on casters, with stainless steel drip trays.

Our BW line includes stainless steel valves (1" BSP), inlet and outlet sight glass, and  $40 \times 40 \text{ cm}$  food-grade Noryl plastic plates which are steam sterilizable.

Our ME line comes complete with Pump and 20  $\times$  20 cm food grade NORYL plates which are also steam sterilizable.

A dividing head is also an option, which allows for 2-stage (double) filtration. Double filtration allows for your product to pass through a coarse filter media, and then also through a polishing filter media while passing through the press only once. Not only does this save you time, but it also reduces the amount of product agitation and handling.

#### STANDARD FEATURES

- Stainless steel head and tail plate
- · Food-grade NORYL plates
- · Pressure gauges inlet & outlet\*
- · Site Glass\* inlet & outlet
- Stainless steel valves
- Stainless steel inlet and outlet connections
- \* BW Press only \*\* Already included on ME Press

### **OPTIONAL FEATURES**

- Moplen Plates
- Expandable
- · Dividing Head (Double Filtrartion)
- Tubing
- Pump & Motor\*\*



## **COMMON APPLICATIONS:**

- · Distilled Beverages
- Beer
- Wine
- · Oils & Vinegars
- Flavors

## **PRODUCT TESTING**

Product testing is always available either at your facility, through our network of distributors, or at our in-house laboratory.

### TECHNICAL DATA

| Max Operateing Pressure    | 70 psi (5 bar)       |
|----------------------------|----------------------|
| Max Differential Pressure  | 40 psi (2.8 bar)     |
| Max Operating Temp. NORYL  | 150° F (65° C)       |
| Max Operating Temp. Moplen | 122° F (50° C)       |
| BW Filter Area per Sheet   | 1.43 ft <sup>2</sup> |
| ME Filter Area per Sheet   | 0.4 ft²              |

## FILTER MEDIA

ErtelAlsop offers the widest varieties of filter media including 100% cellulose pads, cellulose and diatomaceous earth pads, cellulose and Celpure® diatomaceous earth pads, cellulose and perlite pads, and cellulose and activated carbon pads.

All filter pads are manufactured to very high standards for a wide range of applications in the food and beverage, pharmaceutical, chemical, cosmetic, and electric utility markets. ErtelAlsop also offers a Validation Guide to assist in the validation of its filter pads in your process. The Validation Guide contains information regarding raw materials, extractables, and general information about the product.

| MODEL               | BW-19  | BW-29  | BW-39  | BW-49  |
|---------------------|--|--|--|--|
| Standard Height     | 39 in (99 cm)                                |
| Standard Width      | 24.1 in (61.21 cm)                           |
| Standard Length     | 66.8 in (170 cm)                             | 66.8 in (170 cm)                             | 78.6 in (200 cm)                             | 86.3 in (219 cm)                             |
| Standard Weight     | 449 lbs (226 kg)                             | 529 lbs (240 kg)                             | 657 lbs (298 kg)                             | 742 lbs (337 kg)                             |
| Plate Dimension     | 15.2 in x 15.2 in (38.6 x 38.6 cm)           | 15.2 in x 15.2 in (38.6 x 38.6 cm)           | 15.2 in x 15.2 in (38.6 x 38.6 cm)           | 15.2 in x 15.2 in (38.6 x 38.6 cm)           |
| Ports               | 4 External                                   | 4 External                                   | 4 External                                   | 4 External                                   |
| Depth Filter Sheets | 19   | 29   | 39   | 49   |
| Filter Area         | 28.12 ft <sup>2</sup> (0.80 m <sup>2</sup> ) | 49.92 ft <sup>2</sup> (1.22 m <sup>2</sup> ) | 57.72 ft <sup>2</sup> (1.63 m <sup>2</sup> ) | 72.52 ft <sup>2</sup> (2.05 m <sup>2</sup> ) |
| Max Filter Area*    | 45.88 ft <sup>2</sup> (1.30 m <sup>2</sup> ) | 45.88 ft <sup>2</sup> (1.30 m <sup>2</sup> ) | 63.64 ft <sup>2</sup> (1.80 m <sup>2</sup> ) | 78.44 ft <sup>2</sup> (2.22 m <sup>2</sup> ) |

<sup>\*</sup> With the purchase of additional plates

| MODEL               | ME-10                                      | ME-20                                      | ME-30                                      |
|---------------------|--|--|--|
| Standard Height     | 19 in (49 cm)                              | 23 in (57 cm)                              | 23 in (57 cm)                              |
| Standard Width      | 12.5 in (32 cm)                            | 13.8 in (35 cm)                            | 13.8 in (35 cm)                            |
| Standard Length     | 20.5 in (52 cm)                            | 27.8 in (91 cm)                            | 35.7 in (91 cm)                            |
| Standard Weight     | 58 lbs (26 kg)                             | 73 lbs (33 kg)                             | 88 lbs (40 kg)                             |
| Plate Dimension     | 7.9 in x 7.9 in<br>(20 x 20 cm)            | 7.9 in x 7.9 in<br>(20 x 20 cm)            | 7.9 in x 7.9 in<br>(20 x 20 cm)            |
| Ports               | 2 External                                 | 2 External                                 | 2 External                                 |
| Depth Filter Sheets | 10   | 20   | 30   |
| Filter Area         | 0.4 ft <sup>2</sup> (0.03 m <sup>2</sup> ) | 0.4 ft <sup>2</sup> (0.03 m <sup>2</sup> ) | 0.4 ft <sup>2</sup> (1.03 m <sup>2</sup> ) |







For additional product information visit ErtelAlsop.com

**Technical Bulletin BEV-PF-16** 

ErtelAlsop 132 Flatbush Avenue Kingston, NY 12401 US

ErtelAlsop.com 800.553.7835 Telephone 845.853.1526 Fax Keep in touch.

ErtelAlsop.com

Your Local Distributor

Nova Filtration Technologies Inc. 1367 Osprey Drive Unit 1 Ancaster ON L9G4V5

www.novafiltrationtech.com

info@novafiltrationtech.com Tel: (905) 304-8157