HARMSCO®

Filter Housing Selection Guide





SB and **HP** Hurricane® Housings

Industrial/Municipal (SB) Commercial (HP)

- Combination cyclone separator and cartridge filter in a single design
- Patented Up-flow design
- Flow rates to 1,200 GPM (SB) and to 150 GPM (HP)



View Hurricane® Animation www.youtube.com/watch?v=tOXGsUnhmW4








WB and WB 5x170FL WaterBetter® Housings

Commercial

- Single cartridge design
- Patented Up-flow design
- Coated option available
- Flow rates to 150 GPM (WB) and to 600 GPM (WB 5x170FL)
- Offered in 304/316 stainless steel







HMC Filter Housings




- Built to ASME design standards
- U-Stamp option available
- Standard hold down plates to accept DOE, 222/Flat and 222/Fin style cartridges
- Flow rates to 1,400 GPM
- Offered in 304/316 stainless steel



HMC

HIF Filter Housings

- Patented Up-flow design
- Coated option available
- Flow rates to 800 GPM
- Offered in 304/316 stainless steel





BC and HBC Band Clamp Housings

Commercial

- FNPT, BSTP, Flange and Victaulic connections available (BC series only)
- Patented Up-flow design (BC series only)
- Flow rates to 600 GPM
- Offered in 304/316 stainless steel



FSSS Single Cartridge Housings

Commercial/Industrial

- Designed for 300 PSI
- DOE or 222/Flat configurations available
- Offered in 304/316 stainless steel











HMB, HSB and BCB Bag Housings Industrial/Municipal

- U-Stamp option available (HMB, HSB)
- Standard #1, #2 and Extended bag options
- Flow rates to 2,400 GPM
- Offered in 304/316 stainless steel







Filtration Systems





Specialty Housings





NSF Listed Filter Housings

